

Fits **2005-2012 BMW R1200GS/ADV+2013 ADV**  
with ESA or standard suspension

### Care Instructions:

Clean with soap and water.  
Armor-All works well to restore appearance.

### Tools Required:

Torx T25 Screwdriver  
Wire cutter

### Parts:

MudSling  
2 - zip ties  
2 -16 mm screws  
2- rubber washers

### 1. PLACE THE BIKE ON ITS CENTER STAND ON LEVEL GROUND.

*There is no need to remove the stock spring cover, but you may choose to do so.*

- Looking up at the underseat area, remove the two existing TORX head screws with a T25 driver.



- Install a rubber washers on each of the two screws provided. Place the MudSling in between the shock and rear tire and align the mounting holes with the screws holes on the bike. The side wings will nest up against the left & right frame tubes.

- Install the two screws until the washers seat against the MudSling.



**See LOCTITE WARNING below!**

- Then, tightly install one zip-tie per side and trim excess length. Slide the zip-tie knot inwards so it is out of sight.

**Loctite is not compatible with ABS plastic.** If you use it, be sure it contacts only metal parts! Instead of the liquid form, use **QUICKSTIX 248** to give you better control when applying it to the threads.

**ATTENTION!** Be sure to properly set suspension pre-load for the weight being carried before riding.



WARNING AND DISCLAIMER: All parts manufactured, designed or sold by Machineart Moto ("MaMo") should be installed by a qualified motorcycle technician. The risk of injury is increased by improper installation or misuse of equipment. MaMo's customers must exercise good judgment in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by MaMo, the responsibility of MaMo is limited to a refund of the purchase price or the replacement of the part if MaMo determines the part to be defective, and subject to MaMo's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to MaMo products will void this limited warranty). MaMo, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever except as provided by law. MaMo makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose.